



Documentation for SDK for Java 1.1

Table of Contents

Table of Contents	2
SDK for Java 1.1	5
License	5
Compatibility	5
Sample client	6
Basic concepts	8
Authentication	8
Accessing API	9
Class Hierarchy	13
Auth samples	15
Basics	15
Methods	15
getGrantedRoles	15
getGrantedUsers	16
getMail	17
getName	17
getRoles	18
getRolesByUser	19
getUsers	19
getUsersByRole	20
revokeRole	21
revokeUser	21
grantRole	22
grantUser	23
Document samples	25
Basics	25
Methods	25
createDocument	25
createDocumentSimple	26
deleteDocument	27
getDocumentProperties	28
getContent	28
getContentByVersion	29
getDocumentChildren	30
renameDocument	31
setProperties	32
checkout	33
cancelCheckout	33
forceCancelCheckout	34
isCheckedOut	35
checkin	36
getVersionHistory	37
lock	37
unlock	38
forceUnlock	39
isLocked	40
getLockInfo	40
purgeDocument	41
moveDocument	42

copyDocument	42
restoreVersion	43
purgeVersionHistory	44
getVersionHistorySize	45
isLocked	46
getDocumentPath	46
Folder samples	48
Basics	48
Methods	48
createFolder	48
createFolderSimple	49
getFolderProperties	50
deleteFolder	50
renameFolder	51
moveFolder	51
getFolderChildren	52
isValidFolder	53
getFolderPath	54
Note samples	55
Basics	55
Methods	55
addNote	55
getNote	56
deleteNote	56
setNote	57
listNotes	58
Property samples	60
Basics	60
Methods	60
addCategory	60
removeCategory	61
addKeyword	61
removeKeyword	62
setEncryption	63
unsetEncryption	64
setSigned	64
PropertyGroup samples	66
Basics	66
Methods	66
addGroup	66
removeGroup	67
getGroups	68
getAllGroups	69
getPropertyGroupProperties	69
getPropertyGroupForm	70
setPropertyGroupProperties	71
setPropertyGroupPropertiesSimple	72
hasGroup	74
Repository samples	75
Methods	75
getRootFolder	75
getTrashFolder	75
getTemplatesFolder	76
getPersonalFolder	77

getMailFolder	77
getThesaurusFolder	78
getCategoriesFolder	79
purgeTrash	79
getUpdateMessage	80
getRepositoryUuid	81
hasNode	82
getNodePath	82
getNodeUuid	83
getAppVersion	84
Search samples	85
Basics	85
Methods	88
findByContent	88
findByName	89
findByKeywords	90
find	90
findPaginated	91
findSimpleQueryPaginated	93
findMoreLikeThis	94
getKeywordMap	95
getCategorizedDocuments	96

SDK for Java 1.1

OpenKM SDK for Java is a set of software development tools that allows for the creation of applications for OpenKM. The OpenKM SDK for Java include a Webservices library.

This Webservices library is a complete API layer to access OpenKM through REST Webservices and provides complete compatibility between OpenKM REST Webservices versions minimizing the changes in your code.

License



SDK for Java is licensed under the terms of the [EULA - OpenKM SDK End User License Agreement](#) as published by OpenKM Knowledge Management System S.L.

This program is distributed WITHOUT ANY WARRANTY; without even the implied warranty of MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the [EULA - OpenKM SDK End User License Agreement](#) for more details.

Compatibility



SDK for Java version 1.1 should be used:

- **From OpenKM Professional version 6.2.19 to 6.2.28.**
- **From OpenKM Community version 6.3.0 and upper.**

Sample client

You can make use of the OpenKM Maven Repository and the right SDK version. This is a sample pom.xml configuration:

```
<?xml version="1.0" encoding="UTF-8"?>
<project xmlns="http://maven.apache.org/POM/4.0.0"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xsi:schemaLocation="http://maven.apache.org/POM/4.0.0 http://maven.apache.org/maven-v4_0_0.xsd">
  <modelVersion>4.0.0</modelVersion>

  <groupId>com.openkm.sample</groupId>
  <artifactId>sample</artifactId>
  <version>1.0-SNAPSHOT</version>

  <repositories>
    <repository>
      <id>openkm.com</id>
      <name>OpenKM Maven Repository</name>
      <url>http://maven.openkm.com/maven2</url>
    </repository>
  </repositories>

  <dependencies>
    <dependency>
      <groupId>com.openkm</groupId>
      <artifactId>sdk4j</artifactId>
      <version>1.1</version>
    </dependency>
  </dependencies>
</project>
```

Your first class:

```
import com.openkm.sdk4j.OKMWebservices;
import com.openkm.sdk4j.OKMWebservicesFactory;
import com.openkm.sdk4j.bean.Folder;
import com.openkm.sdk4j.exception.*;

/**
 * Sample OpenKM SDK client
 */
public class Main {
    public static void main(String var[]) throws Exception {
        String url = "http://demo.openkm.com/OpenKM";
        String user = "user5";
        String pass = "pass5";
        OKMWebservices okm = OKMWebservicesFactory.newInstance(url, user, pass);

        for (Folder fld : okm.getFolderChildren("/okm:root")) {
            System.out.println("Folder -> " + fld.getPath());
        }
    }
}
```


Basic concepts

Authentication

The first lines in your Java code should be used to create the Webservices object.

We suggest using this method:

```
OKMWebservices ws = OKMWebservicesFactory.newInstance(host,
username, password);
```

```
package com.openkm;

import com.openkm.sdk4j.OKMWebservices;
import com.openkm.sdk4j.OKMWebservicesFactory;
import com.openkm.sdk4j.exception.AccessDeniedException;
import com.openkm.sdk4j.exception.DatabaseException;
import com.openkm.sdk4j.exception.RepositoryException;
import com.openkm.sdk4j.exception.UnknowException;
import com.openkm.sdk4j.exception.WebServiceException;

public class Test {
    public static void main(String[] args) {
        String host = "http://localhost:8080/OpenKM";
        String username = "okmAdmin";
        String password = "admin";
        OKMWebservices ws = OKMWebservicesFactory.newInstance(host, usern

        try {
            System.out.println(ws.getAppVersion());
        } catch (RepositoryException e) {
            e.printStackTrace();
        } catch (DatabaseException e) {
            e.printStackTrace();
        } catch (UnknowException e) {
            e.printStackTrace();
        } catch (WebServiceException e) {
            e.printStackTrace();
        }
    }
}
```

Also is possible doing the same from each API class implementation.



We do not suggest this way.

For example with this method:

```
RepositoryImpl repositoryImpl = new RepositoryImpl(host,
```



```
username, password, new BeanHelper());
```

```
package com.openkm;

import com.openkm.sdk4j.OKMWebservices;
import com.openkm.sdk4j.OKMWebservicesFactory;
import com.openkm.sdk4j.exception.AccessDeniedException;
import com.openkm.sdk4j.exception.DatabaseException;
import com.openkm.sdk4j.exception.RepositoryException;
import com.openkm.sdk4j.exception.UnknowException;
import com.openkm.sdk4j.exception.WebServiceException;
import com.openkm.sdk4j.impl.RepositoryImpl;
import com.openkm.sdk4j.util.BeanHelper;

public class Test {
    public static void main(String[] args) {
        String host = "http://localhost:8080/OpenKM";
        String username = "okmAdmin";
        String password = "admin";
        RepositoryImpl repositoryImpl = new RepositoryImpl(host, username

        try {
            System.out.println(repositoryImpl.getAppVersion());
        } catch (RepositoryException e) {
            e.printStackTrace();
        } catch (DatabaseException e) {
            e.printStackTrace();
        } catch (UnknowException e) {
            e.printStackTrace();
        } catch (WebServiceException e) {
            e.printStackTrace();
        }
    }
}
```

Accessing API

OpenKM API classes are under com.openkm package, as can shown at this [Javadoc API summary](#).



At main url <http://docs.openkm.com/javadoc/> you'll see all available Javadoc documentation.

At the moment of writing this page the actual OpenKM version was 6.3.0 what can change on time.



There is a direct correspondence between the classes and methods into, implemented at com.openkm.api packages and available from SDK for Java.

OpenKM API classes:

OpenKM API class	Description	Supported	Implementation	Int

OKMAuth	Manage security and users. For example add or remove grants on a node, create or modify users or getting the profiles.	Yes	AuthImpl.java	BaseAuth
OKMBookmark	Manage the user bookmarks.	No		
OKMDashboard	Manage all data shown at dashboard.	No		
OKMDocument	Manage documents. For example create, move or delete a document.	Yes	DocumentImpl.java	BaseDocu
OKMFolder	Manage folders. For example create, move	Yes	FolderImpl.java	BaseFolde

	or delete a folder.			
OKMMail	Manage mails. For example create, move or delete a mails.	No		
OKMNote	Manage notes on any node type. For example create, edit or delete a note on a document, folder, mail or record.	Yes	NoteImpl.java	BaseNote.
OKMNotification	Manage notifications. For example add or remove subscriptions on a document or a folder.	No		
OKMProperty	Manage	Yes	PropertyImpl.java	BasePropert

	<p>categories and keywords. For example add or remove keywords on a document, folder, mail or record.</p>			
OKMPropertyGroup	<p>Manage metadata. For example add metadata group, set metadata fields.</p>	Yes	PropertyGroupImpl.java	BasePropo
OKMRepository	<p>A lot of stuff related with repository. For example get the properties of main root node (/okm:root).</p>	Yes	RepositoryImpl.java	BaseRepo
OKMSearch	<p>Manage search</p>	Yes	SearchImpl.java	BaseSearch

	feature. For example manage saved queries or perform a new query to the repository.			
OKMStats	General stats of the repository.	No		
OKMUserConfig	Manage user home configuration.	No		

Class Hierarchy

Packages detail:

Name	Description
com.openkm	<p>The com.openkm.OKMWebservicesFactory that returns an com.openkm.OKMWebservices object which implements all interfaces.</p> <pre>OKMWebservices ws = OKMWebservicesFactory.newInstance(host, username, password);</pre>
com.openkm.sdk4j.bean	Contains all classes result of unmarshalling REST objects.
com.openkm.sdk4j.definition	All interface classes:

	<ul style="list-style-type: none">● <code>com.openkm.sdk4j.definition.BaseAuth</code>● <code>com.openkm.sdk4j.definition.BaseDocument</code>● <code>com.openkm.sdk4j.definition.BaseFolder</code>● <code>com.openkm.sdk4j.definition.BaseNote</code>● <code>com.openkm.sdk4j.definition.BaseProperty</code>● <code>com.openkm.sdk4j.definition.BasePropertyGroup</code>● <code>com.openkm.sdk4j.definition.BaseRepository</code>● <code>com.openkm.sdk4j.definition.BaseSearch</code>
<code>com.openkm.sdk4j.impl</code>	All interface implementation classes: <ul style="list-style-type: none">● <code>com.openkm.sdk4j.impl.AuthImpl</code>● <code>com.openkm.sdk4j.impl.DocumentImpl</code>● <code>com.openkm.sdk4j.impl.FolderImpl</code>● <code>com.openkm.sdk4j.impl.NoteImpl</code>● <code>com.openkm.sdk4j.impl.PropertyGroupImpl</code>● <code>com.openkm.sdk4j.impl.PropertyImpl</code>● <code>com.openkm.sdk4j.impl.RepositoryImpl</code>● <code>com.openkm.sdk4j.impl.SearchImpl</code>
<code>com.openkm.sdk4j.util</code>	A couple of utilities. <div data-bbox="639 1518 1401 1697" style="border: 1px dashed #00aaff; border-radius: 10px; padding: 10px; margin-top: 10px;"> The class <code>com.openkm.sdk4j.util.ISO8601</code> should be used to set and parse metadata date fields.</div>
<code>com.openkm.sdk4j.exception</code>	All exception classes.

Auth samples

Basics

The class **com.openkm.sdk4j.bean.Permission** contains permission values (READ, WRITE, etc.). You should use it in combination with methods that are changing or getting security grants.

 To set READ and WRITE access you should do:

```
int permission = Permission.READ + Permission.WRITE;
```

To check if you have permission access you should do:

```
// permission is a valid integer value
if ((permission | Permission.WRITE) = Permission.WRITE) {
    // Has WRITE grants.
}
```

On almost methods you'll see parameter named "**nodeId**". The value of this parameter can be some valid node **UUID** (folder, document, mail, record) or node **path**.

 Example of nodeId:

- Using UUID -> "**c41f9ea0-0d6c-45da-bae4-d72b66f42d0f**";
- Using path -> "**/okm:root/sample.pdf**"

Methods

getGrantedRoles

Description:

Method	Return values	Description
getGrantedRoles(String nodeId)	Map<String, Integer>	Returns the granted roles of a node.

Example:

```

package com.openkm;

import java.util.Map;

import com.openkm.sdk4j.OKMWebservices;
import com.openkm.sdk4j.OKMWebservicesFactory;

public class Test {
    public static void main(String[] args) {
        String host = "http://localhost:8080/OpenKM";
        String username = "okmAdmin";
        String password = "admin";
        OKMWebservices ws = OKMWebservicesFactory.newInstance(host,

        try {
            Map<String, Integer> grants = ws.getGrantedRoles("/okm:
            for (String role : grants.keySet()) {
                System.out.println(role + "->" + grants.get(role));
            }
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
}

```

getGrantedUsers**Description:**

Method	Return values	Description
getGrantedUsers(String nodeId)	Map<String, Integer>	Returns the granted users of a node.

Example:

```

package com.openkm;

import java.util.Map;

import com.openkm.sdk4j.OKMWebservices;
import com.openkm.sdk4j.OKMWebservicesFactory;

public class Test {
    public static void main(String[] args) {
        String host = "http://localhost:8080/OpenKM";
        String username = "okmAdmin";
        String password = "admin";
        OKMWebservices ws = OKMWebservicesFactory.newInstance(host,

        try {

```



```

        Map<String, Integer> grants = ws.getGrantedUsers("/okm:
        for (String role : grants.keySet()) {
            System.out.println(role + "->" + grants.get(role));
        }
    } catch (Exception e) {
        e.printStackTrace();
    }
}
}
}

```

getMail

Description:

Method	Return values	Description
getMail(String user)	String	Returns the mail of a valid user.

Example:

```

package com.openkm;

import com.openkm.sdk4j.OKMWebservices;
import com.openkm.sdk4j.OKMWebservicesFactory;

public class Test {
    public static void main(String[] args) {
        String host = "http://localhost:8080/OpenKM";
        String username = "okmAdmin";
        String password = "admin";
        OKMWebservices ws = OKMWebservicesFactory.newInstance(host,

        try {
            System.out.println(ws.getMail("okmAdmin"));
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
}

```

getName

Description:

Method	Return values	Description
getName(String user)	String	Returns the name of a valid user.

Example:

```
package com.openkm;

import com.openkm.sdk4j.OKMWebservices;
import com.openkm.sdk4j.OKMWebservicesFactory;

public class Test {
    public static void main(String[] args) {
        String host = "http://localhost:8080/OpenKM";
        String username = "okmAdmin";
        String password = "admin";
        OKMWebservices ws = OKMWebservicesFactory.newInstance(host,

        try {
            System.out.println(ws.getName("okmAdmin"));
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
}
```

getRoles

Description:

Method	Return values	Description
getRoles()	List<String>	Returns the list of all the roles.

Example:

```
package com.openkm;

import com.openkm.sdk4j.OKMWebservices;
import com.openkm.sdk4j.OKMWebservicesFactory;

public class Test {
    public static void main(String[] args) {
        String host = "http://localhost:8080/OpenKM";
        String username = "okmAdmin";
        String password = "admin";
        OKMWebservices ws = OKMWebservicesFactory.newInstance(host,

        try {
            for (String role : ws.getRoles()) {
                System.out.println(role);
            }
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
}
```

getRolesByUser

Description:

Method	Return values	Description
getRolesByUser(String user)	List<String>	Returns the list of all the roles assigned to a user.

Example:

```

package com.openkm;

import com.openkm.sdk4j.OKMWebservices;
import com.openkm.sdk4j.OKMWebservicesFactory;

public class Test {
    public static void main(String[] args) {
        String host = "http://localhost:8080/OpenKM";
        String username = "okmAdmin";
        String password = "admin";
        OKMWebservices ws = OKMWebservicesFactory.newInstance(host,

        try {
            for (String role : ws.getRolesByUser("okmAdmin")) {
                System.out.println(role);
            }
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
}
    
```

getUsers

Description:

Method	Return values	Description
getUsers()	List<String>	Returns the list of all the users.

Example:

```

package com.openkm;

import com.openkm.sdk4j.OKMWebservices;
import com.openkm.sdk4j.OKMWebservicesFactory;
    
```

```
public class Test {
    public static void main(String[] args) {
        String host = "http://localhost:8080/OpenKM";
        String username = "okmAdmin";
        String password = "admin";
        OKMWebservices ws = OKMWebservicesFactory.newInstance(host,

        try {
            for (String user : ws.getUsers()) {
                System.out.println(user);
            }
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
}
```

getUsersByRole

Description:

Method	Return values	Description
getUsersByRole(String role)	List<String>	Returns the list of all the users who have assigned a role.

Example:

```
package com.openkm;

import com.openkm.sdk4j.OKMWebservices;
import com.openkm.sdk4j.OKMWebservicesFactory;

public class Test {
    public static void main(String[] args) {
        String host = "http://localhost:8080/OpenKM";
        String username = "okmAdmin";
        String password = "admin";
        OKMWebservices ws = OKMWebservicesFactory.newInstance(host,

        try {
            for (String user : ws.getUsersByRole("ROLE_ADMIN")) {
                System.out.println(user);
            }
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
}
```

revokeRole

Description:

Method	Return values	Description
revokeRole(String nodeId, String role, int permissions, boolean recursive)	void	Removes role grant on a node.
<p>The parameter recursive only has sense when the nodeId is a folder or record node.</p> <p>When parameter recursive is true, the change will be applied to the node and descendants.</p>		

Example:

```

package com.openkm;

import com.openkm.sdk4j.OKMWebservices;
import com.openkm.sdk4j.OKMWebservicesFactory;
import com.openkm.sdk4j.bean.Permission;

public class Test {
    public static void main(String[] args) {
        String host = "http://localhost:8080/OpenKM";
        String username = "okmAdmin";
        String password = "admin";
        OKMWebservices ws = OKMWebservicesFactory.newInstance(host,
        username, password);

        try {
            // Remove ROLE_USER write grants at the node but not de
            ws.revokeRole("/okm:root", "ROLE_USER", Permission.ALL_

            // Remove all ROLE_ADMIN grants to the node and descend
            ws.revokeRole("/okm:root", "ROLE_ADMIN", Permission.ALL_
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
}
    
```

revokeUser

Description:

Method	Return values	Description

revokeUser(String nodeId, String user, int permissions, boolean recursive)	void	Removes user grant on a node.
<p>The parameter recursive only has sense when the nodeId is a folder or record node.</p>		
<p>When parameter recursive is true, the change will be applied to the node and descendants.</p>		

Example:

```

package com.openkm;

import com.openkm.sdk4j.OKMWebservices;
import com.openkm.sdk4j.OKMWebservicesFactory;
import com.openkm.sdk4j.bean.Permission;

public class Test {
    public static void main(String[] args) {
        String host = "http://localhost:8080/OpenKM";
        String username = "okmAdmin";
        String password = "admin";
        OKMWebservices ws = OKMWebservicesFactory.newInstance(host,
        password, username);

        try {
            // Remove john write grants at the node but not descend
            ws.revokeUser("/okm:root", "john", Permission.ALL_GRANTED);

            // Remove all okmAdmin grants at the node and descendant
            ws.revokeUser("/okm:root", "okmAdmin", Permission.ALL_GRANTED);
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
}
    
```

grantRole

Description:

Method	Return values	Description
grantRole(String nodeId, String role, int permissions, boolean recursive)	void	Adds role grant on a node.
<p>The parameter recursive only has sense when the nodeId is a folder or record node.</p>		

When parameter recursive is true, the change will be applied to the node and descendants.

Example:

```
package com.openkm;

import com.openkm.sdk4j.OKMWebservices;
import com.openkm.sdk4j.OKMWebservicesFactory;
import com.openkm.sdk4j.bean.Permission;

public class Test {
    public static void main(String[] args) {
        String host = "http://localhost:8080/OpenKM";
        String username = "okmAdmin";
        String password = "admin";
        OKMWebservices ws = OKMWebservicesFactory.newInstance(host,
        try {
            // Add ROLE_USER write grants at the node but not descen
            ws.grantRole("/okm:root", "ROLE_USER", Permission.ALL_G
            // Add all ROLE_ADMIN grants to the node and descendant
            ws.grantRole("/okm:root", "ROLE_ADMIN", Permission.ALL_
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
}
```

grantUser

Description:

Method	Return values	Description
grantUser(String nodeId, String user, int permissions, boolean recursive)	void	Adds user grant on a node.
<p>The parameter recursive only has sense when the nodeId is a folder or record node.</p> <p>When parameter recursive is true, the change will be applied to the node and descendants.</p>		

Example:

```
package com.openkm;
```

```
import com.openkm.sdk4j.OKMWebservices;
import com.openkm.sdk4j.OKMWebservicesFactory;
import com.openkm.sdk4j.bean.Permission;

public class Test {
    public static void main(String[] args) {
        String host = "http://localhost:8080/OpenKM";
        String username = "okmAdmin";
        String password = "admin";
        OKMWebservices ws = OKMWebservicesFactory.newInstance(host,
        try {
            // Add john write grants at the node but not descendant
            ws.grantUser("/okm:root", "john", Permission.ALL_GRANTS

            // Add all okmAdmin grants at the node and descendants
            ws.grantUser("/okm:root", "okmAdmin", Permission.ALL_GR
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
}
```


Document samples

Basics

On most methods you'll see parameter named "**docId**". The value of this parameter can be some valid document **UUID** or **path**.


 Example of docId:

- Using UUID -> "**f123a950-0329-4d62-8328-0ff500fd42db**";
- Using path -> "**/okm:root/logo.png**"

Methods

createDocument

Description:

Method	Return values	Description
createDocument(Document doc, InputStream is)	Document	Creates a new document and returns as a result an object Document with the properties of the created document.
<p>The variable path into the parameter doc, must be initialized. It indicates where the document must be stored into OpenKM.</p> <div style="border: 1px dashed #42a5f5; padding: 5px; margin: 10px 0;"> <pre>Document doc = new Document (); doc.setPath ("/okm:root/logo.png");</pre> </div> <div style="border: 1px dashed #ffb74d; padding: 10px; margin: 10px 0;"> <p> The other variables of Document (doc) will not take any effect on document creation.</p> <p>We suggest use the method below createDocumentSimple rather this one.</p> </div>		

Example:

```

package com.openkm;

import java.io.FileInputStream;
import java.io.InputStream;

import org.apache.commons.io.IOUtils;

import com.openkm.sdk4j.OKMWebservices;
import com.openkm.sdk4j.OKMWebservicesFactory;
import com.openkm.sdk4j.bean.Document;

public class Test {
    public static void main(String[] args) {
        String host = "http://localhost:8080/OpenKM";
        String username = "okmAdmin";
        String password = "admin";
        OKMWebservices ws = OKMWebservicesFactory.newInstance(host,

        try {
            InputStream is = new FileInputStream("/home/files/logo.
            Document doc = new Document();
            doc.setPath("/okm:root/logo.png");
            ws.createDocument(doc, is);
            IOUtils.closeQuietly(is);
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
}

```

createDocumentSimple

Description:

Method	Return values	Description
createDocumentSimple(String docPath, InputStream is)	Document	Creates a new document and return as a result an object Document with the properties of the created document.

Example:

```

package com.openkm;

import java.io.FileInputStream;
import java.io.InputStream;

import com.openkm.sdk4j.OKMWebservices;
import com.openkm.sdk4j.OKMWebservicesFactory;

```


```
public class Test {
    public static void main(String[] args) {
        String host = "http://localhost:8080/OpenKM";
        String username = "okmAdmin";
        String password = "admin";
        OKMWebservices ws = OKMWebservicesFactory.newInstance(host,

        try {
            InputStream is = new FileInputStream("/home/files/logo.
            ws.createDocumentSimple("/okm:root/logo.png", is);
            IOUtils.closeQuietly(is);
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
}
```

deleteDocument

Description:

Method	Return values	Description
deleteDocument(String docId)	void	Delete a document.

 When a document is deleted is automatically moved to /okm:trash/userId folder.

Example:

```
package com.openkm;

import com.openkm.sdk4j.OKMWebservices;
import com.openkm.sdk4j.OKMWebservicesFactory;

public class Test {
    public static void main(String[] args) {
        String host = "http://localhost:8080/OpenKM";
        String username = "okmAdmin";
        String password = "admin";
        OKMWebservices ws = OKMWebservicesFactory.newInstance(host,

        try {
            ws.deleteDocument("/okm:root/logo.png");
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
}
```

getDocumentProperties

Description:

Method	Return values	Description
getDocumentProperties(String docId)	Document	Returns the document properties.

Example:

```

package com.openkm;

import com.openkm.sdk4j.OKMWebservices;
import com.openkm.sdk4j.OKMWebservicesFactory;


public class Test {
    public static void main(String[] args) {
        String host = "http://localhost:8080/OpenKM";
        String username = "okmAdmin";
        String password = "admin";
        OKMWebservices ws = OKMWebservicesFactory.newInstance(host,

        try {
            System.out.println(ws.getDocumentProperties("/okm:root/
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
}
    
```

getContent

Description:


Method	Return values	Descrip
getContent(String docId)	InputStream	Retrieves the document content - binary data



In case you sent the file across a Servlet response we suggest set the content lenght with

```

Document doc = ws.getDocumentProperties("/okm:root/logo.p
response.setContentLength(new Long(doc.getActualVersion()
    
```



We've found wrong size problems while using:

```
response.setContentLength(is.available());
```

Example:

```
package com.openkm;

import java.io.FileOutputStream;
import java.io.InputStream;
import java.io.OutputStream;

import org.apache.commons.io.IOUtils;

import com.openkm.sdk4j.OKMWebservices;
import com.openkm.sdk4j.OKMWebservicesFactory;


public class Test {
    public static void main(String[] args) {
        String host = "http://localhost:8080/OpenKM";
        String username = "okmAdmin";
        String password = "admin";
        OKMWebservices ws = OKMWebservicesFactory.newInstance(host,

        try {
            OutputStream fos = new FileOutputStream("/home/files/logo.png");
            InputStream is = ws.getContent("/okm:root/logo.png");
            IOUtils.copy(is, fos);
            IOUtils.closeQuietly(is);
            IOUtils.closeQuietly(fos);
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
}
```

getContentByVersion


Description:

Method	Return values
getContentByVersion(String docId, String versionId)	<div style="display: flex; align-items: center;"> <div style="margin-right: 20px;">InputStream</div> <div>Retrieves document content document version.</div> </div>



In case you sent the file across a Servlet response we suggest set the content length with

```
Document doc = ws.getDocumentProperties("/okm:root/logo.p
response.setContentLength(new Long(doc.getActualVersion()
```



We've found wrong size problems while using:

```
response.setContentLength(is.available());
```

Example:

```
package com.openkm;

import java.io.FileOutputStream;
import java.io.InputStream;
import java.io.OutputStream;

import org.apache.commons.io.IOUtils;

import com.openkm.sdk4j.OKMWebservices;
import com.openkm.sdk4j.OKMWebservicesFactory;

public class Test {
    public static void main(String[] args) {
        String host = "http://localhost:8080/OpenKM";
        String username = "okmAdmin";
        String password = "admin";
        OKMWebservices ws = OKMWebservicesFactory.newInstance(host,

        try {
            OutputStream fos = new FileOutputStream("/home/files/logo.png");
            InputStream is = ws.getContentByVersion("/okm:root/logo.png", "1.0");
            IOUtils.copy(is, fos);
            IOUtils.closeQuietly(is);
            IOUtils.closeQuietly(fos);
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
}
```

getDocumentChildren

Description:

Method	Return values	Description

getDocumentChildren(String fldId)	List<Document>	Returns a list of all documents which their parent is fldId.
The parameter fldId can be a folder or a record node.		

Example:

```

package com.openkm;

import com.openkm.sdk4j.OKMWebservices;
import com.openkm.sdk4j.OKMWebservicesFactory;
import com.openkm.sdk4j.bean.Document;

public class Test {
    public static void main(String[] args) {
        String host = "http://localhost:8080/OpenKM";
        String username = "okmAdmin";
        String password = "admin";
        OKMWebservices ws = OKMWebservicesFactory.newInstance(host,
            username, password);

        try {
            for (Document doc : ws.getDocumentChildren("/okm:root"))
                System.out.println(doc);
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
}
    
```

renameDocument

Description:

Method	Return values	Description
renameDocument(String docId, String newName)	void	Change the name of a document.

Example:

```

package com.openkm;

import com.openkm.sdk4j.OKMWebservices;
import com.openkm.sdk4j.OKMWebservicesFactory;

public class Test {
    
```

```

public static void main(String[] args) {
    String host = "http://localhost:8080/OpenKM";
    String username = "okmAdmin";
    String password = "admin";
    OKMWebservices ws = OKMWebservicesFactory.newInstance(host,

    try {
        ws.renameDocument("f123a950-0329-4d62-8328-0ff500fd42db
    } catch (Exception e) {
        e.printStackTrace();
    }
}
}

```


setProperties

Description:

Method	Return values	Description
setProperties(Document doc)	void	Change some document properties.

Variables allowed to be changed:

- Title
- Associated keywords


Only not null and not empty variables will be take on consideration.

Example:

```

package com.openkm;

import com.openkm.sdk4j.OKMWebservices;
import com.openkm.sdk4j.OKMWebservicesFactory;
import com.openkm.sdk4j.bean.Document;

public class Test {
    public static void main(String[] args) {
        String host = "http://localhost:8080/OpenKM";
        String username = "okmAdmin";
        String password = "admin";
        OKMWebservices ws = OKMWebservicesFactory.newInstance(host,

        try {
            Document doc = ws.getDocumentProperties("f123a950-0329-
            doc.setDescription("some description");
            doc.getKeywords().add("test");
        }
    }
}

```



```

        ws.setProperties(doc);
    } catch (Exception e) {
        e.printStackTrace();
    }
}
}
}

```

checkout

Description:

Method	Return values	Description
checkout(String docId)	void	Marks the document for edition.

Only one user can modify a document at the same time.

Before starting edition must do a checkout action that lock the edition process for other users and allows only to the user who has executed the action.

Example:

```

package com.openkm;

import com.openkm.sdk4j.OKMWebservices;
import com.openkm.sdk4j.OKMWebservicesFactory;

public class Test {
    public static void main(String[] args) {
        String host = "http://localhost:8080/OpenKM";
        String username = "okmAdmin";
        String password = "admin";
        OKMWebservices ws = OKMWebservicesFactory.newInstance(host,

        try {
            ws.checkout("/okm:root/logo.png");
            // At this point the document is locked for other users
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
}
}


```

cancelCheckout

Description:

Method	Return values	Description
--------	---------------	-------------

cancelCheckout(String docId)	void	Cancel a document edition.
-------------------------------------	-------------	----------------------------



This action can only be done by the user who previously executed the checkout action.

Example:

```

package com.openkm;

import com.openkm.sdk4j.OKMWebservices;
import com.openkm.sdk4j.OKMWebservicesFactory;

public class Test {
    public static void main(String[] args) {
        String host = "http://localhost:8080/OpenKM";
        String username = "okmAdmin";
        String password = "admin";
        OKMWebservices ws = OKMWebservicesFactory.newInstance(host,

        try {
            // At this point the document is locked for other users
            ws.cancelCheckout("/okm:root/logo.png");
            // At this point other users are allowed to execute a c
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
}
    
```


forceCancelCheckout

Description:

Method	Return values	Description
forceCancelCheckout(String docId)	void	Cancel a document edition.

This method allows to cancel edition of any document.

It is not mandatory to execute this action by the same user who previously executed the checkout action.



This action can only be done by a super user (user with ROLE_ADMIN).

Example:

```

package com.openkm;

import com.openkm.sdk4j.OKMWebservices;
import com.openkm.sdk4j.OKMWebservicesFactory;

public class Test {
    public static void main(String[] args) {
        String host = "http://localhost:8080/OpenKM";
        String username = "okmAdmin";
        String password = "admin";
        OKMWebservices ws = OKMWebservicesFactory.newInstance(host,

    try {
        // At this point the document is locked for other users
        ws.forceCancelCheckout("/okm:root/logo.png");
        // At this point other users are allowed to execute a c
    } catch (Exception e) {
        e.printStackTrace();
    }
}
}

```

isCheckedOut

Description:

Method	Return values	Description
isCheckedOut(String docId)	Boolean	Returns a boolean that indicate if the document is on edition or not.

Example:

```

package com.openkm;

import com.openkm.sdk4j.OKMWebservices;
import com.openkm.sdk4j.OKMWebservicesFactory;

public class Test {
    public static void main(String[] args) {
        String host = "http://localhost:8080/OpenKM";
        String username = "okmAdmin";
        String password = "admin";
        OKMWebservices ws = OKMWebservicesFactory.newInstance(host,

    try {
        System.out.println("Is the document checkout:"+ws.isChe

```


```

    } catch (Exception e) {
        e.printStackTrace();
    }
}
}
}

```

checkin

Description:

Method	Return values	Description
checkin(String docId, InputStream is, String comment)	Version	Updates a document with new version and return an object with new Version values.
 Only the user who started the edition - checkout - is allowed to update the document.		

Example:

```

package com.openkm;

import java.io.FileInputStream;
import java.io.InputStream;

import org.apache.commons.io.IOUtils;

import com.openkm.sdk4j.OKMWebservices;
import com.openkm.sdk4j.OKMWebservicesFactory;

public class Test {
    public static void main(String[] args) {
        String host = "http://localhost:8080/OpenKM";
        String username = "okmAdmin";
        String password = "admin";
        OKMWebservices ws = OKMWebservicesFactory.newInstance(host,

        try {
            InputStream is = new FileInputStream("/home/files/logo.png");
            ws.checkin("/okm:root/logo.png", is, "optional some comment");
            IOUtils.closeQuietly(is);
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
}
}

```

getVersionHistory

Description:

Method	Return values	Description
getVersionHistory(String docId)	List<Version>	Returns a list of all document versions.

Example:

```

package com.openkm;

import com.openkm.sdk4j.OKMWebservices;
import com.openkm.sdk4j.OKMWebservicesFactory;
import com.openkm.sdk4j.bean.Version;


public class Test {
    public static void main(String[] args) {
        String host = "http://localhost:8080/OpenKM";
        String username = "okmAdmin";
        String password = "admin";
        OKMWebservices ws = OKMWebservicesFactory.newInstance(host,
            username, password);

        try {
            for (Version version : ws.getVersionHistory("/okm:root/")) {
                System.out.println(version);
            }
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
}
    
```

lock

Description:

Method	Return values	Description
lock(String docId)	LockInfo	Locks a document and return an object with the Lock information.



Only the user who locked the document is allowed to unlock.

A locked document can not be modified by other users.

Example:

```

package com.openkm;

import com.openkm.sdk4j.OKMWebservices;
import com.openkm.sdk4j.OKMWebservicesFactory;

public class Test {
    public static void main(String[] args) {
        String host = "http://localhost:8080/OpenKM";
        String username = "okmAdmin";
        String password = "admin";
        OKMWebservices ws = OKMWebservicesFactory.newInstance(host,


        try {
            ws.lock("/okm:root/logo.png");
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
}

```

unlock

Description:

Method	Return values	Description
unlock(String docId)	void	Unlocks a locked document.



Only the user who locked the document is allowed to unlock.

Example:

```

package com.openkm;

import com.openkm.sdk4j.OKMWebservices;
import com.openkm.sdk4j.OKMWebservicesFactory;

public class Test {
    public static void main(String[] args) {
        String host = "http://localhost:8080/OpenKM";
        String username = "okmAdmin";
        String password = "admin";
        OKMWebservices ws = OKMWebservicesFactory.newInstance(host,

```

```

        try {
            ws.unlock("/okm:root/logo.png");
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
}

```


forceUnlock

Description:

Method	Return values	Description
forceUnlock(String docId)	void	Unlocks a locked document.

This method allows to unlock any locked document.

It is not mandatory execute this action by the same user who previously executed the checkout lock action.


This action can only be done by a super user (user with ROLE_ADMIN).

Example:

```

package com.openkm;

import com.openkm.sdk4j.OKMWebservices;
import com.openkm.sdk4j.OKMWebservicesFactory;

public class Test {
    public static void main(String[] args) {
        String host = "http://localhost:8080/OpenKM";
        String username = "okmAdmin";
        String password = "admin";
        OKMWebservices ws = OKMWebservicesFactory.newInstance(host,

        try {
            ws.forceUnlock("/okm:root/logo.png");
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
}

```

isLocked

Description:

Method	Return values	Description
isLocked(String docId)	Boolean	Returns a boolean that indicate if the document is locked or not.

Example:

```

package com.openkm;

import com.openkm.sdk4j.OKMWebservices;
import com.openkm.sdk4j.OKMWebservicesFactory;

public class Test {
    public static void main(String[] args) {
        String host = "http://localhost:8080/OpenKM";
        String username = "okmAdmin";
        String password = "admin";
        OKMWebservices ws = OKMWebservicesFactory.newInstance(host,
        username, password);

        try {
            System.out.println("Is document locked:"+ws.isLocked("/"));
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
}
    
```

getLockInfo

Description:

Method	Return values	Description
getLockInfo(String docId)	LockInfo	Returns an object with the Lock information

Example:

```

package com.openkm;

import com.openkm.sdk4j.OKMWebservices;
import com.openkm.sdk4j.OKMWebservicesFactory;

public class Test {
    public static void main(String[] args) {
        String host = "http://localhost:8080/OpenKM";
    }
}
    
```



```
String username = "okmAdmin";
String password = "admin";
OKMWebservices ws = OKMWebservicesFactory.newInstance(host,


try {
    System.out.println(ws.getLockInfo("/okm:root/logo.png")
} catch (Exception e) {
    e.printStackTrace();
}
}
```

purgeDocument

Description:

Method	Return values	Description
purgeDocument(String docId)	void	Document is definitely removed from repository.

Usually you will purge documents into /okm:trash/userId - the personal trash user locations - but is possible to directly purge any document from the whole repository.



When a document is purged only will be able to be restored from a previously repository backup. The purge action remove the document definitely from the repository.

Example:

```
package com.openkm;

import com.openkm.sdk4j.OKMWebservices;
import com.openkm.sdk4j.OKMWebservicesFactory;

public class Test {
    public static void main(String[] args) {
        String host = "http://localhost:8080/OpenKM";
        String username = "okmAdmin";
        String password = "admin";
        OKMWebservices ws = OKMWebservicesFactory.newInstance(host,

        try {
            ws.purgeDocument("/okm:trash/okmAdmin/logo.png");
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
}
```

```

    }
}

```

moveDocument

Description:

Method	Return values	Description
moveDocument(String docId, String dstId)	void	Moves a document into some folder or record.
The values of the dstId parameter should be a folder or record UUID or path.		

Example:

```

package com.openkm;

import com.openkm.sdk4j.OKMWebservices;
import com.openkm.sdk4j.OKMWebservicesFactory;

public class Test {
    public static void main(String[] args) {
        String host = "http://localhost:8080/OpenKM";
        String username = "okmAdmin";
        String password = "admin";
        OKMWebservices ws = OKMWebservicesFactory.newInstance(host,
        username, password);

        try {
            ws.moveDocument("/okm:root/logo.png", "/okm:root/temp");
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
}


```

copyDocument

Description:

Method	Return values	Description
copyDocument(String docId, String dstId)	void	Copies a document into some folder or record.

The values of the `dstId` parameter should be a folder or record UUID or path.



Only the binary data and the security grants are copied to destination, the metadata, keywords, etc. of the document are not copied.

Example:

```

package com.openkm;

import com.openkm.sdk4j.OKMWebservices;
import com.openkm.sdk4j.OKMWebservicesFactory;

public class Test {
    public static void main(String[] args) {
        String host = "http://localhost:8080/OpenKM";
        String username = "okmAdmin";
        String password = "admin";
        OKMWebservices ws = OKMWebservicesFactory.newInstance(host,

        try {
            ws.copyDocument("/okm:root/logo.png", "/okm:root/temp");
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
}
    
```

restoreVersion

Description:

Method	Return values	Description
restoreVersion(String docId, String versionId)	void	Promotes a previous document version to actual version.

Example:

```

package com.openkm;

import com.openkm.sdk4j.OKMWebservices;
import com.openkm.sdk4j.OKMWebservicesFactory;

public class Test {
    public static void main(String[] args) {
        String host = "http://localhost:8080/OpenKM";
        String username = "okmAdmin";
    }
}
    
```

```
String password = "admin";
OKMWebservices ws = OKMWebservicesFactory.newInstance(host,


try {
    // Actual version is 1.2
    ws.restoreVersion("/okm:root/logo.png", "1.1");
    // Actual version is 1.1
} catch (Exception e) {
    e.printStackTrace();
}
}
```

purgeVersionHistory

Description:

Method	Return values	Description
purgeVersionHistory(String docId)	void	Purges all documents version except the actual version.

This action compact the version history of a document.

 **This action can not be reverted.**

Example:

```
package com.openkm;

import com.openkm.sdk4j.OKMWebservices;
import com.openkm.sdk4j.OKMWebservicesFactory;

public class Test {
    public static void main(String[] args) {
        String host = "http://localhost:8080/OpenKM";
        String username = "okmAdmin";
        String password = "admin";
        OKMWebservices ws = OKMWebservicesFactory.newInstance(host,

        try {
            // Version history has version 1.3,1.2,1.1 and 1.0
            ws.purgeVersionHistory("/okm:root/logo.png");
            // Version history has only version 1.3
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
}
```

```
}
```

getVersionHistorySize

Description:

Method	Return values	Description
getVersionHistorySize(String docId)	long	Returns the sum in bytes of all documents into documents history.

Example:

```
package com.openkm;

import java.util.Locale;

import com.openkm.sdk4j.OKMWebservices;
import com.openkm.sdk4j.OKMWebservicesFactory;

public class Test {
    public static void main(String[] args) {
        String host = "http://localhost:8080/OpenKM";
        String username = "okmAdmin";
        String password = "admin";
        OKMWebservices ws = OKMWebservicesFactory.newInstance(host,
        password);

        try {
            String[] UNITS = new String[] { "B", "KB", "MB", "GB", "TB", "PB" };
            long bytes = ws.getVersionHistorySize("/okm:root/logo.ppt");
            String value = "";

            for (int i = 6; i > 0; i--) {
                double step = Math.pow(1024, i);
                if (bytes > step)
                    value = String.format(Locale.ROOT, "%3.1f %s",
                    (float) bytes / step, UNITS[i]);
            }

            if (value.isEmpty()) {
                value = Long.toString(bytes) + " " + UNITS[0];
            }

            System.out.println(value);
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
}
```

isLocked

Description:

Method	Return values	Description
isValidDocument(String docId)	Boolean	Returns a boolean that indicate if the node is a document or not.

Example:

```

package com.openkm;

import com.openkm.sdk4j.OKMWebservices;
import com.openkm.sdk4j.OKMWebservicesFactory;

public class Test {
    public static void main(String[] args) {
        String host = "http://localhost:8080/OpenKM";
        String username = "okmAdmin";
        String password = "admin";
        OKMWebservices ws = OKMWebservicesFactory.newInstance(host,

        try {
            // Return true
            ws.isValidDocument("/okm:root/logo.png");

            // Return false
            ws.isValidDocument("/okm:root");
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
}
    
```

getDocumentPath

Description:

Method	Return values	Description
getDocumentPath(String uuid)	String	Converts a document UUID to document path.

Example:

```

package com.openkm;
    
```

```
import com.openkm.sdk4j.OKMWebservices;
import com.openkm.sdk4j.OKMWebservicesFactory;

public class Test {
    public static void main(String[] args) {
        String host = "http://localhost:8080/OpenKM";
        String username = "okmAdmin";
        String password = "admin";
        OKMWebservices ws = OKMWebservicesFactory.newInstance(host,

        try {
            System.out.println(ws.getDocumentPath("f123a950-0329-4d
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
}
```

Folder samples

Basics

On most methods you'll see parameter named "**fldId**". The value of this parameter can be some valid folder **UUID** or **path**.


 Example of fldId:

- Using UUID -> "**f123a950-0329-4d62-8328-0ff500fd42db**";
- Using path -> "**/okm:root/test**"

Methods

createFolder

Description:

Method	Return values	Description
createFolder(Folder fld)	Folder	Creates a new folder and returns as a result an object Folder.
<p>The variable path into the parameter fld, must be initialized. It indicates the folder path into OpenKM.</p> <div style="border: 1px dashed #007bff; padding: 5px; margin: 5px 0;"> <pre>Folder fld = new Folder(); fld.setPath("/okm:root/test");</pre> </div> <div style="border: 1px dashed #ffc107; padding: 5px; margin: 5px 0;"> <p> The other variables of Folder (fld) will not take any effect on folder creation.</p> <p>We suggest using the method below to create FolderSimple rather this one.</p> </div>		

Example:

```
package com.openkm;
```



```

import com.openkm.sdk4j.OKMWebservices;
import com.openkm.sdk4j.OKMWebservicesFactory;
import com.openkm.sdk4j.bean.Folder;

public class Test {
    public static void main(String[] args) {
        String host = "http://localhost:8080/OpenKM";
        String username = "okmAdmin";
        String password = "admin";
        OKMWebservices ws = OKMWebservicesFactory.newInstance(host,

        try {
            Folder fld = new Folder();
            fld.setPath("/okm:root/test");
            ws.createFolder(fld);
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
}

```

createFolderSimple

Description:

Method	Return values	Description
createFolderSimple(String fldPath)	Folder	Creates a new folder and returns as a result an object Folder.

Example:

```

package com.openkm;

import com.openkm.sdk4j.OKMWebservices;
import com.openkm.sdk4j.OKMWebservicesFactory;
import com.openkm.sdk4j.bean.Folder;

public class Test {
    public static void main(String[] args) {
        String host = "http://localhost:8080/OpenKM";
        String username = "okmAdmin";
        String password = "admin";
        OKMWebservices ws = OKMWebservicesFactory.newInstance(host,

        try {
            ws.createFolderSimple("/okm:root/test");
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
}

```

getFolderProperties

Description:

Method	Return values	Description
getFolderProperties(String fldId)	Folder	Returns the folder properties.

Example:

```

package com.openkm;

import com.openkm.sdk4j.OKMWebservices;
import com.openkm.sdk4j.OKMWebservicesFactory;

public class Test {
    public static void main(String[] args) {
        String host = "http://localhost:8080/OpenKM";
        String username = "okmAdmin";
        String password = "admin";
        OKMWebservices ws = OKMWebservicesFactory.newInstance(host,

        try {
            System.out.println(ws.getFolderProperties("/okm:root/te
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
}

```

deleteFolder

Description:

Method	Return values	Description
deleteFolder(String fldId)	void	Deletes a folder.

Example:

```

package com.openkm;

import com.openkm.sdk4j.OKMWebservices;
import com.openkm.sdk4j.OKMWebservicesFactory;

public class Test {
    public static void main(String[] args) {
        String host = "http://localhost:8080/OpenKM";
        String username = "okmAdmin";

```

```
String password = "admin";
OKMWebservices ws = OKMWebservicesFactory.newInstance(host,

try {
    ws.deleteFolder("/okm:root/test");
} catch (Exception e) {
    e.printStackTrace();
}
}
```

renameFolder

Description:

Method	Return values	Description
renameFolder(String fldId, String newName)	void	Renames a folder.

Example:

```
package com.openkm;

import com.openkm.sdk4j.OKMWebservices;
import com.openkm.sdk4j.OKMWebservicesFactory;

public class Test {
    public static void main(String[] args) {
        String host = "http://localhost:8080/OpenKM";
        String username = "okmAdmin";
        String password = "admin";
        OKMWebservices ws = OKMWebservicesFactory.newInstance(host,

        try {
            // Exists folder /okm:root/test
            ws.renameFolder("/okm:root/test", "renamedFolder");
            // Folder has renamed to /okm:root/renamedFolder
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
}
```

moveFolder

Description:

Method	Return values	Description
moveFolder(String fldId, String		Moves folder into some folder or

dstId)	void	record.
The values of the dstId parameter should be a folder or record UUID or path.		

Example:

```

package com.openkm;

import com.openkm.sdk4j.OKMWebservices;
import com.openkm.sdk4j.OKMWebservicesFactory;

public class Test {
    public static void main(String[] args) {
        String host = "http://localhost:8080/OpenKM";
        String username = "okmAdmin";
        String password = "admin";
        OKMWebservices ws = OKMWebservicesFactory.newInstance(host,

        try {
            // Exists folder /okm:root/test
            ws.moveFolder("/okm:root/test", "/okm:root/tmp");
            // Folder has moved to /okm:root/tmp/test
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
}
    
```

getFolderChildren

Description:

Method	Return values	Description
getFolderChildren(String fldId)	List<Folder>	Returns a list of all folder which their parent is fldId.
The parameter fldId can be a folder or a record node.		

Example:

```

package com.openkm;

import com.openkm.sdk4j.OKMWebservices;
import com.openkm.sdk4j.OKMWebservicesFactory;
import com.openkm.sdk4j.bean.Folder;
    
```

```
public class Test {
    public static void main(String[] args) {
        String host = "http://localhost:8080/OpenKM";
        String username = "okmAdmin";
        String password = "admin";
        OKMWebservices ws = OKMWebservicesFactory.newInstance(host,

        try {
            for (Folder fld : ws.getFolderChildren("/okm:root")) {
                System.out.println(fld);
            }
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
}
```

isValidFolder

Description:

Method	Return values	Description
isValidFolder(String fldId)	Boolean	Returns a boolean that indicates if the node is a folder or not.

Example:

```
package com.openkm;

import com.openkm.sdk4j.OKMWebservices;
import com.openkm.sdk4j.OKMWebservicesFactory;

public class Test {
    public static void main(String[] args) {
        String host = "http://localhost:8080/OpenKM";
        String username = "okmAdmin";
        String password = "admin";
        OKMWebservices ws = OKMWebservicesFactory.newInstance(host,

        try {
            // Return false
            ws.isValidFolder("/okm:root/logo.png");

            // Return true
            ws.isValidFolder("/okm:root");
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
}
```

getFolderPath

Description:

Method	Return values	Description
getFolderPath(String uuid)	String	Converts folder UUID to folder path.

Example:

```
package com.openkm;  
  
import com.openkm.sdk4j.OKMWebservices;  
import com.openkm.sdk4j.OKMWebservicesFactory;  
  
public class Test {  
    public static void main(String[] args) {  
        String host = "http://localhost:8080/OpenKM";  
        String username = "okmAdmin";  
        String password = "admin";  
        OKMWebservices ws = OKMWebservicesFactory.newInstance(host,  
  
        try {  
            System.out.println(ws.getFolderPath("f123a950-0329-4d62  
        } catch (Exception e) {  
            e.printStackTrace();  
        }  
    }  
}
```

Note samples

Basics

On most methods you'll see parameter named "**nodeId**". The value of this parameter can be a valid document, folder, mail or record **UUID** or **path**.

 Example of nodeId:

- Using UUID -> "**f123a950-0329-4d62-8328-0ff500fd42db**";
- Using path -> "**/okm:root/logo.png**"

Methods

addNote

Description:

Method	Return values	Description
addNote(String nodeId, String text)	Note	Adds a note to a node and returns an object Note.

Example:

```
package com.openkm;

import com.openkm.sdk4j.OKMWebservices;
import com.openkm.sdk4j.OKMWebservicesFactory;

public class Test {
    public static void main(String[] args) {
        String host = "http://localhost:8080/OpenKM";
        String username = "okmAdmin";
        String password = "admin";
        OKMWebservices ws = OKMWebservicesFactory.newInstance(host,

        try {
            ws.addNote("/okm:root/logo.png", "the note text");
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
}
```

getNote

Description:

Method	Return values	Description
getNote(String noteId)	Note	Retrieves the note.

i The noteId is an UUID.

The object Node has a variable named path, in that case the path contains an UUID.

Example:

```

package com.openkm;

import java.util.List;

import com.openkm.sdk4j.OKMWebservices;
import com.openkm.sdk4j.OKMWebservicesFactory;
import com.openkm.sdk4j.bean.Note;

public class Test {
    public static void main(String[] args) {
        String host = "http://localhost:8080/OpenKM";
        String username = "okmAdmin";
        String password = "admin";
        OKMWebservices ws = OKMWebservicesFactory.newInstance(host,
        username, password);

        try {
            List<Note> notes = ws.listNotes("/okm:root/logo.png");
            if (notes.size() > 0) {
                System.out.println(ws.getNote(notes.get(0).getPath());
            }
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
}
    
```

deleteNote

Description:

Method	Return values	Description

deleteNote(String noteId)	Note	Deletes a note.
----------------------------------	-------------	-----------------

i The noteId is an UUID.

The object Node has a variable named path, in that case the path contains an UUID.

Example:

```

package com.openkm;

import java.util.List;

import com.openkm.sdk4j.OKMWebservices;
import com.openkm.sdk4j.OKMWebservicesFactory;
import com.openkm.sdk4j.bean.Note;

public class Test {
    public static void main(String[] args) {
        String host = "http://localhost:8080/OpenKM";
        String username = "okmAdmin";
        String password = "admin";
        OKMWebservices ws = OKMWebservicesFactory.newInstance(host,

        try {
            List<Note> notes = ws.listNotes("/okm:root/logo.png");
            if (notes.size() > 0) {
                ws.deleteNote(notes.get(0).getPath());
            }
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
}
    
```

setNote

Description:

Method	Return values	Description
setNote(String noteId, String text)	void	Change the note text.

i The noteId is an UUID.

The object Node has a variable named path, in that case the path contains an UUID.

Example:

```

package com.openkm;

import java.util.List;

import com.openkm.sdk4j.OKMWebservices;
import com.openkm.sdk4j.OKMWebservicesFactory;
import com.openkm.sdk4j.bean.Note;

public class Test {
    public static void main(String[] args) {
        String host = "http://localhost:8080/OpenKM";
        String username = "okmAdmin";
        String password = "admin";
        OKMWebservices ws = OKMWebservicesFactory.newInstance(host,

        try {
            List<Note> notes = ws.listNotes("/okm:root/logo.png");
            if (notes.size() > 0) {
                ws.setNote(notes.get(0).getPath(), "text modified")
            }
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
}

```

listNotes

Description:

Method	Return values	Description
listNotes(String nodeId)	List<Note>	Retrieves a list of all notes of a node.

Example:

```

package com.openkm;

import java.util.List;

import com.openkm.sdk4j.OKMWebservices;
import com.openkm.sdk4j.OKMWebservicesFactory;
import com.openkm.sdk4j.bean.Note;

public class Test {
    public static void main(String[] args) {
        String host = "http://localhost:8080/OpenKM";
        String username = "okmAdmin";
        String password = "admin";

```

```
OKMWebservices ws = OKMWebservicesFactory.newInstance(host,
try {
    List<Note> notes = ws.listNotes("/okm:root/logo.png");
    for (Note note : notes) {
        System.out.println(note);
    }
} catch (Exception e) {
    e.printStackTrace();
}
}
```

Property samples

Basics

On most methods you'll see parameter named "**nodeId**". The value of this parameter can be a valid document, folder, mail or record **UUID** or **path**.



Example of nodeId:

- Using UUID -> "**f123a950-0329-4d62-8328-0ff500fd42db**";
- Using path -> "**/okm:root/logo.png**"

Methods

addCategory

Description:

Method	Return values	Description
addCategory(String nodeId, String catId)	void	Sets a relation between a category and a node.
The value of the catId parameter should be a category folder UUID or path.		

Example:

```
package com.openkm;

import com.openkm.sdk4j.OKMWebservices;
import com.openkm.sdk4j.OKMWebservicesFactory;

public class Test {
    public static void main(String[] args) {
        String host = "http://localhost:8080/OpenKM";
        String username = "okmAdmin";
        String password = "admin";
        OKMWebservices ws = OKMWebservicesFactory.newInstance(host,

        try {
            ws.addCategory("/okm:root/logo.png", "/okm:categories/t
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
}
```

```

    }
}
}

```

removeCategory

Description:

Method	Return values	Description
removeCategory(String nodeId, String catId)	void	Removes a relation between a category and a node.
The value of the catId parameter should be a category folder UUID or path.		

Example:

```

package com.openkm;

import com.openkm.sdk4j.OKMWebservices;
import com.openkm.sdk4j.OKMWebservicesFactory;

public class Test {
    public static void main(String[] args) {
        String host = "http://localhost:8080/OpenKM";
        String username = "okmAdmin";
        String password = "admin";
        OKMWebservices ws = OKMWebservicesFactory.newInstance(host,

        try {
            ws.removeCategory("/okm:root/logo.png", "/okm:category
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
}

```


addKeyword

Description:

Method	Return values	Description
addKeyword(String nodeId, String keyword)	void	Adds a keyword and a node.

The keyword should be a single word without spaces, formats allowed:

- "test"
- "two_words" (the character "_" is used for the junction).


Also we suggest you to add keyword in lower case format, because OpenKM is case sensitive.

Example:

```
package com.openkm;

import com.openkm.sdk4j.OKMWebservices;
import com.openkm.sdk4j.OKMWebservicesFactory;

public class Test {
    public static void main(String[] args) {
        String host = "http://localhost:8080/OpenKM";
        String username = "okmAdmin";
        String password = "admin";
        OKMWebservices ws = OKMWebservicesFactory.newInstance(host,

        try {
            ws.addKeyword("/okm:root/logo.png", "test");
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
}
```

removeKeyword

Description:

Method	Return values	Description
removeKeyword(String nodeId, String keyword)	void	Removes a keyword from a node.

Example:

```
package com.openkm;
```


```
import com.openkm.sdk4j.OKMWebservices;
import com.openkm.sdk4j.OKMWebservicesFactory;

public class Test {
    public static void main(String[] args) {
        String host = "http://localhost:8080/OpenKM";
        String username = "okmAdmin";
        String password = "admin";
        OKMWebservices ws = OKMWebservicesFactory.newInstance(host,

        try {
            ws.removeKeyword("/okm:root/logo.png", "test");
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
}
```

setEncryption

Description:

Method	Return values	Description
setEncryption(String nodeId, String cipherName)	void	Marks a document as an encrypted binary data into the repository
<p>The parameter nodeId should be a document node.</p> <p>The parameter cipherName saves information about the encryption mechanism.</p> <div style="border: 1px dashed orange; padding: 10px; background-color: #fff9c4;">  <p>This method does not perform any kind of encryption, simply marks the database that a document is encrypted.</p> </div>		

Example:

```
package com.openkm;

import com.openkm.sdk4j.OKMWebservices;
import com.openkm.sdk4j.OKMWebservicesFactory;

public class Test {
    public static void main(String[] args) {
        String host = "http://localhost:8080/OpenKM";
        String username = "okmAdmin";
        String password = "admin";
        OKMWebservices ws = OKMWebservicesFactory.newInstance(host,
```


```

        try {
            ws.setEncryption("/okm:root/logo.png", "phrase");
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
}

```

unsetEncryption

Description:

Method	Return values	Description
unsetEncryption(String nodeId)	void	Marks a document as a normal binary data into repository.
<p>The parameter nodeId should be a document node.</p> <div style="border: 1px dashed orange; padding: 10px; background-color: #fff9c4;">  <p>This method does not perform any kind of unryption, simply mark the database that a document has been unrypted.</p> </div>		

Example:

```

package com.openkm;

import com.openkm.sdk4j.OKMWebservices;
import com.openkm.sdk4j.OKMWebservicesFactory;

public class Test {
    public static void main(String[] args) {
        String host = "http://localhost:8080/OpenKM";
        String username = "okmAdmin";
        String password = "admin";
        OKMWebservices ws = OKMWebservicesFactory.newInstance(host);

        try {
            ws.unsetEncryption("/okm:root/logo.png");
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
}


```

setSigned

Description:

Method	Return values	Description
setSigned(String nodeId, boolean signed)	void	Marks a document as signed or unsigned binary data into the repository

The parameter nodeId should be a document node.

 This method does not perform any kind of digital signature process, simply marks the database that a document is signed.

Example:

```
package com.openkm;  
  
import com.openkm.sdk4j.OKMWebservices;  
import com.openkm.sdk4j.OKMWebservicesFactory;  
  
public class Test {  
    public static void main(String[] args) {  
        String host = "http://localhost:8080/OpenKM";  
        String username = "okmAdmin";  
        String password = "admin";  
        OKMWebservices ws = OKMWebservicesFactory.newInstance(host,  
  
        try {  
            ws.setSigned("/okm:root/logo.pdf", true);  
        } catch (Exception e) {  
            e.printStackTrace();  
        }  
    }  
}
```

PropertyGroup samples

Basics



From older OpenKM version we named "Metadata Groups" as "Property Groups".

Although we understand this name not helps a lot to identifying these methods with metadata ones, for historical reason, we continue mantaining the nomenclature.

For more information about [Metadata](#).

On almost methods you'll see parameter named "nodeId". The value of this parameter can be a valid document, folder, mail or record **UUID** or **path**.



Example of nodeId:

- Using UUID -> "f123a950-0329-4d62-8328-0ff500fd42db";
- Using path -> "/okm:root/logo.png"



The class `com.openkm.sdk4j.util.ISO8601` should be used to set and parse metadata date fields. The metadata field of type date values are stored into application in ISO-8601 basic format.

To convert retrieved metadata field of type date to a valid date use:

```
Calendar cal = ISO8601.parseBasic(metadataFieldValue);
```

To save date value into metadata field of type date use:

```
Calendar cal = Calendar.getInstance(); // Present date
String metadataFieldValue = ISO8601.formatBasic(cal);
// metadataFieldValue can be saved into repository metadata
```

Methods

addGroup

Description:

Method	Return values	Description
--------	---------------	-------------

addGroup(String nodeId, String grpName)	void	Adds an empty metadata group to a node.
The grpName should be a valid Metadata group name.		

Example:

```

package com.openkm;

import com.openkm.sdk4j.OKMWebservices;
import com.openkm.sdk4j.OKMWebservicesFactory;

public class Test {
    public static void main(String[] args) {
        String host = "http://localhost:8080/OpenKM";
        String username = "okmAdmin";
        String password = "admin";
        OKMWebservices ws = OKMWebservicesFactory.newInstance(host);

        try {
            ws.addGroup("/okm:root/logo.pdf", "okg:consulting");
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
}
    
```

removeGroup

Description:

Method	Return values	Description
removeGroup(String nodeId, String grpName)	void	Removes a metadata group of a node.
The grpName should be a valid Metadata group name.		

Example:

```

package com.openkm;
    
```

```
import com.openkm.sdk4j.OKMWebservices;
import com.openkm.sdk4j.OKMWebservicesFactory;

public class Test {
    public static void main(String[] args) {
        String host = "http://localhost:8080/OpenKM";
        String username = "okmAdmin";
        String password = "admin";
        OKMWebservices ws = OKMWebservicesFactory.newInstance(host,

        try {
            ws.removeGroup("/okm:root/logo.pdf", "okg:consulting");
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
}
```

getGroups

Description:

Method	Return values	Description
getGroups(String nodeId)	List<PropertyGroup>	Retrieves a list of metadata groups assigned to a node.

Example:

```
package com.openkm;

import com.openkm.sdk4j.OKMWebservices;
import com.openkm.sdk4j.OKMWebservicesFactory;
import com.openkm.sdk4j.bean.PropertyGroup;

public class Test {
    public static void main(String[] args) {
        String host = "http://localhost:8080/OpenKM";
        String username = "okmAdmin";
        String password = "admin";
        OKMWebservices ws = OKMWebservicesFactory.newInstance(host,

        try {
            for (PropertyGroup pGroup : ws.getGroups("/okm:root/logo.pdf")) {
                System.out.println(pGroup);
            }
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
}
```

getAllGroups

Description:

Method	Return values	Description
getAllGroups()	List<PropertyGroup>	Retrieves a list of all metadata groups set into the application.

Example:

```

package com.openkm;

import com.openkm.sdk4j.OKMWebservices;
import com.openkm.sdk4j.OKMWebservicesFactory;
import com.openkm.sdk4j.bean.PropertyGroup;

public class Test {
    public static void main(String[] args) {
        String host = "http://localhost:8080/OpenKM";
        String username = "okmAdmin";
        String password = "admin";
        OKMWebservices ws = OKMWebservicesFactory.newInstance(host);

        try {
            for (PropertyGroup pGroup : ws.getAllGroups()) {
                System.out.println(pGroup);
            }
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
}
    
```

getPropertyGroupProperties

Description:

Method	Return values	Description
getPropertyGroupProperties(String nodeId, String grpName)	List<FormElement>	Retrieves a list of all metadata group elements and its values of a node.

The grpName should be a valid Metadata group name.



The method is usually used to display form elements with its values to be shown or changed by used.

Example:

```
package com.openkm;

import com.openkm.sdk4j.OKMWebservices;
import com.openkm.sdk4j.OKMWebservicesFactory;
import com.openkm.sdk4j.bean.form.FormElement;

public class Test {
    public static void main(String[] args) {
        String host = "http://localhost:8080/OpenKM";
        String username = "okmAdmin";
        String password = "admin";
        OKMWebservices ws = OKMWebservicesFactory.newInstance(host,

    try {
        for (FormElement fElement : ws.getPropertyGroupProperties())
            System.out.println(fElement);
        }
    } catch (Exception e) {
        e.printStackTrace();
    }
}
}
```

getPropertyGroupForm

Description:

Method	Return values	Description
getPropertyGroupForm(String grpName)	List<FormElement>	Retrieves a list of all metadata group elements definition.

The grpName should be a valid Metadata group name.



The method is usually used to display empty form elements for creating new metadata values.

Example:

```

package com.openkm;

import com.openkm.sdk4j.OKMWebservices;
import com.openkm.sdk4j.OKMWebservicesFactory;
import com.openkm.sdk4j.bean.form.FormElement;

public class Test {
    public static void main(String[] args) {
        String host = "http://localhost:8080/OpenKM";
        String username = "okmAdmin";
        String password = "admin";
        OKMWebservices ws = OKMWebservicesFactory.newInstance(host,

        try {
            for (FormElement fElement : ws.getPropertyGroupForm("ok
                System.out.println(fElement);
            }
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
}
    
```

setPropertyGroupProperties

Description:

Method	Return values
setPropertyGroupProperties(String nodeId, String grpName, List<FormElement> ofeList)	void

The grpName should be a valid Metadata group name.

i Is not mandatory set into parameter ofeList all FormElement, is enough with the form E

i The sample below is based on this Metadata group definition:

```

<?xml version="1.0" encoding="UTF-8"?>
<!DOCTYPE property-groups PUBLIC "-//OpenKM//DTD Property
    "http://www.openkm.com/c
<property-groups>
  <property-group label="Consulting" name="okg:consulting
    <input label="Name" type="text" name="okp:consulting.
    <input label="Date" type="date" name="okp:consulting.
    <checkbox label="Important" name="okp:consulting.impc
    <textarea label="Comment" name="okp:consulting.commer
  </property-group>
    
```

```
</property-groups>
```

Example:

```
package com.openkm;

import java.util.ArrayList;
import java.util.List;

import com.openkm.sdk4j.OKMWebservices;
import com.openkm.sdk4j.OKMWebservicesFactory;
import com.openkm.sdk4j.bean.form.FormElement;
import com.openkm.sdk4j.bean.form.Input;

public class Test {
    public static void main(String[] args) {
        String host = "http://localhost:8080/OpenKM";
        String username = "okmAdmin";
        String password = "admin";
        OKMWebservices ws = OKMWebservicesFactory.newInstance(host,

        try {
            // Modify with a full FormElement list
            List<FormElement> fElements = ws.getPropertyGroupProperties(
            for (FormElement fElement : fElements) {
                if (fElement.getName().equals("okp:consulting.name")
                    Input name = (Input) fElement;
                    name.setValue("new value");
                }
            }

            ws.setPropertyGroupProperties("/okm:root/logo.pdf", "ok

            // Same modification with only affected FormElement
            fElements = new ArrayList<>();
            Input name = new Input();
            name.setName("okp:consulting.name");
            name.setValue("new value");
            fElements.add(name);
            ws.setPropertyGroupProperties("/okm:root/logo.pdf", "okg
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
}
```

setPropertyGroupPropertiesSimple**Description:**

Method	Return value

setPropertyGroupPropertiesSimple(String nodeId, String grpName, Map<String, String> properties)

void

The grpName should be a valid Metadata group name.



Is not mandatory set into properties parameter all fields values, is enough with the fields



The sample below is based on this Metadata group definition:

```
<?xml version="1.0" encoding="UTF-8"?>
<!DOCTYPE property-groups PUBLIC "-//OpenKM//DTD Property
    "http://www.openkm.com/c
<property-groups>
  <property-group label="Consulting" name="okg:consulting
    <input label="Name" type="text" name="okp:consulting.
    <input label="Date" type="date" name="okp:consulting.
    <checkbox label="Important" name="okp:consulting.impc
    <textarea label="Comment" name="okp:consulting.commer
  </property-group>
</property-groups>
```



To add several values on a metadata field of type multiple like this:

```
<select label="Multiple" name="okp:consulting.multiple" t
  <option label="One" value="one"/>
  <option label="Two" value="two"/>
  <option label="Three" value="three" />
</select>
```

You should do:

```
properties.put("okp:consulting.multiple", "one;two");
```

Where **"one"** and **"two"** are valid values and character ";" is used as separator.

Example:

```
package com.openkm;

import java.util.Calendar;
import java.util.HashMap;
import java.util.Map;
```

```
import com.openkm.sdk4j.OKMWebservices;
import com.openkm.sdk4j.OKMWebservicesFactory;
import com.openkm.sdk4j.util.ISO8601;

public class Test {
    public static void main(String[] args) {
        String host = "http://localhost:8080/OpenKM";
        String username = "okmAdmin";
        String password = "admin";
        OKMWebservices ws = OKMWebservicesFactory.newInstance(host,

        try {
            Map<String, String> properties = new HashMap<>();
            properties.put("okp:consulting.name", "new name");

            // Date fields must be saved with basic ISO 8601 format
            properties.put("okp:consulting.date", ISO8601.formatBas
            ws.setPropertyGroupPropertiesSimple("/okm:root/logo.pdf
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
}
```

hasGroup

Description:

Method	Return values	Description
hasGroup(String nodeId, String grpName)	Boolean	Returns a boolean that indicate if the node has or not a metadata group.

Example:

```
package com.openkm;

import com.openkm.sdk4j.OKMWebservices;
import com.openkm.sdk4j.OKMWebservicesFactory;

public class Test {
    public static void main(String[] args) {
        String host = "http://localhost:8080/OpenKM";
        String username = "okmAdmin";
        String password = "admin";
        OKMWebservices ws = OKMWebservicesFactory.newInstance(host,

        try {
            System.out.println("Have metadata group:" + ws.hasGroup
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
}
```

```
}  
}
```

Repository samples

Methods

getRootFolder

Description:

Method	Return values	Description
getRootFolder()	Folder	Returns the object Folder of node "/okm:root"

Example:

```

package com.openkm;

import com.openkm.sdk4j.OKMWebservices;
import com.openkm.sdk4j.OKMWebservicesFactory;

public class Test {
    public static void main(String[] args) {
        String host = "http://localhost:8080/OpenKM";
        String username = "okmAdmin";
        String password = "admin";
        OKMWebservices ws = OKMWebservicesFactory.newInstance(host,
            username, password);

        try {
            System.out.println(ws.getRootFolder());
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
}
    
```

getTrashFolder

Description:

Method	Return values	Description
getTrashFolder()	Folder	Returns the object Folder of node "/okm:trash/{userId}"
<p>The returned folder will be the user trash folder.</p>		



For example if the method is executed by "okmAdmin" user then the folder returned will be "/okm:trash/okmAdmin".

Example:

```
package com.openkm;

import com.openkm.sdk4j.OKMWebservices;
import com.openkm.sdk4j.OKMWebservicesFactory;

public class Test {
    public static void main(String[] args) {
        String host = "http://localhost:8080/OpenKM";
        String username = "okmAdmin";
        String password = "admin";
        OKMWebservices ws = OKMWebservicesFactory.newInstance(host,

        try {
            System.out.println(ws.getTrashFolder());
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
}
```

getTemplatesFolder

Description:

Method	Return values	Description
getTemplatesFolder()	Folder	Returns the object Folder of node "/okm:templates"

Example:

```
package com.openkm;

import com.openkm.sdk4j.OKMWebservices;
import com.openkm.sdk4j.OKMWebservicesFactory;

public class Test {
    public static void main(String[] args) {
        String host = "http://localhost:8080/OpenKM";
        String username = "okmAdmin";
        String password = "admin";
        OKMWebservices ws = OKMWebservicesFactory.newInstance(host,

        try {
            System.out.println(ws.getTemplatesFolder());
        }
    }
}
```

```

        } catch (Exception e) {
            e.printStackTrace();
        }
    }
}

```

getPersonalFolder

Description:

Method	Return values	Description
getPersonalFolder()	Folder	Returns the object Folder of node "/okm:personal/{userId}"
<p>The returned folder will be the user personal folder.</p> <div style="border: 1px dashed blue; border-radius: 10px; padding: 10px; background-color: #e0f0ff;"> <p>i For example if the method is executed by "okmAdmin" user then the folder returned will be "/okm:personal/okmAdmin".</p> </div>		

Example:

```

package com.openkm;

import com.openkm.sdk4j.OKMWebservices;
import com.openkm.sdk4j.OKMWebservicesFactory;

public class Test {
    public static void main(String[] args) {
        String host = "http://localhost:8080/OpenKM";
        String username = "okmAdmin";
        String password = "admin";
        OKMWebservices ws = OKMWebservicesFactory.newInstance(host,

        try {
            System.out.println(ws.getPersonalFolder());
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
}

```


getMailFolder

Description:

Method	Return	Description
--------	--------	-------------

values		
getMailFolder()	Folder	Returns the object Folder of node "/okm:mail/{userId}"

The returned folder will be the user mail folder.



For example if the method is executed by "okmAdmin" user then the folder returned will be "/okm:mail/okmAdmin".

Example:

```

package com.openkm;

import com.openkm.sdk4j.OKMWebservices;
import com.openkm.sdk4j.OKMWebservicesFactory;

public class Test {
    public static void main(String[] args) {
        String host = "http://localhost:8080/OpenKM";
        String username = "okmAdmin";
        String password = "admin";
        OKMWebservices ws = OKMWebservicesFactory.newInstance(host,

        try {
            System.out.println(ws.getMailFolder());
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
}
    
```

getThesaurusFolder

Description:

Method	Return values	Description
getThesaurusFolder()	Folder	Returns the object Folder of node "/okm:thesaurus"

Example:

```

package com.openkm;

import com.openkm.sdk4j.OKMWebservices;
    
```

```
import com.openkm.sdk4j.OKMWebservicesFactory;

public class Test {
    public static void main(String[] args) {
        String host = "http://localhost:8080/OpenKM";
        String username = "okmAdmin";
        String password = "admin";
        OKMWebservices ws = OKMWebservicesFactory.newInstance(host,

        try {
            System.out.println(ws.getThesaurusFolder());
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
}
```

getCategoriesFolder

Description:

Method	Return values	Description
getCategoriesFolder()	Folder	Returns the object Folder of node "/okm:categories"

Example:

```
package com.openkm;

import com.openkm.sdk4j.OKMWebservices;
import com.openkm.sdk4j.OKMWebservicesFactory;


public class Test {
    public static void main(String[] args) {
        String host = "http://localhost:8080/OpenKM";
        String username = "okmAdmin";
        String password = "admin";
        OKMWebservices ws = OKMWebservicesFactory.newInstance(host,


        try {
            System.out.println(ws.getCategoriesFolder());
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
}
```

purgeTrash

Description:

Method	Return values	Description
purgeTrash()	void	Definitively removes from repository all nodes into "/okm:trash/{userId}"

 For example if the method is executed by "okmAdmin" user then the purged trash will be "/okm:trash/okmAdmin".

 When a node is purged, it only will be able to be restored from a previously repository backup. The purge action remove the node definitely from the repository.

Example:

```

package com.openkm;

import com.openkm.sdk4j.OKMWebservices;
import com.openkm.sdk4j.OKMWebservicesFactory;

public class Test {
    public static void main(String[] args) {
        String host = "http://localhost:8080/OpenKM";
        String username = "okmAdmin";
        String password = "admin";
        OKMWebservices ws = OKMWebservicesFactory.newInstance(host,


        try {
            ws.purgeTrash();
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
}
    
```

getUpdateMessage

Description:

Method	Return values	Description
getUpdateMessage()	String	Retrieves a message in case there is a newer OpenKM release.

There's an official OpenKM update message service available which is based on your local OpenKM version.

 The most common message is that a new OpenKM version has been released.

Example:

```
package com.openkm;

import com.openkm.sdk4j.OKMWebservices;
import com.openkm.sdk4j.OKMWebservicesFactory;

public class Test {
    public static void main(String[] args) {
        String host = "http://localhost:8080/OpenKM";
        String username = "okmAdmin";
        String password = "admin";
        OKMWebservices ws = OKMWebservicesFactory.newInstance(host,

        try {
            System.out.println(ws.getUpdateMessage());
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
}
```

getRepositoryUuid

Description:

Method	Return values	Description
getRepositoryUuid()	String	Retrieves installation unique identifier.

Example:

```
package com.openkm;

import com.openkm.sdk4j.OKMWebservices;
import com.openkm.sdk4j.OKMWebservicesFactory;

public class Test {
    public static void main(String[] args) {
        String host = "http://localhost:8080/OpenKM";
        String username = "okmAdmin";
        String password = "admin";
```

```

        OKMWebservices ws = OKMWebservicesFactory.newInstance(host,
        try {
            System.out.println(ws.getRepositoryUuid());
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
}

```

hasNode

Description:

Method	Return values	Description
hasNode(String nodeId)	Boolean	Returns a node that indicate if a node exists or not.
The value of the parameter nodeId can be a valid UUID or path .		

Example:

```

package com.openkm;

import com.openkm.sdk4j.OKMWebservices;
import com.openkm.sdk4j.OKMWebservicesFactory;

public class Test {
    public static void main(String[] args) {
        String host = "http://localhost:8080/OpenKM";
        String username = "okmAdmin";
        String password = "admin";
        OKMWebservices ws = OKMWebservicesFactory.newInstance(host,

        try {
            System.out.println("Exists node:"+ws.hasNode("064ff51a-
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
}

```

getNodePath

Description:

Method	Return values	Description


```
}  
}
```

getAppVersion

Description:

Method	Return values	Description
getAppVersion()	AppVersion	Returns information about OpenKM version.

Example:

```
package com.openkm;  
  
import com.openkm.sdk4j.OKMWebservices;  
import com.openkm.sdk4j.OKMWebservicesFactory;  
  
public class Test {  
    public static void main(String[] args) {  
        String host = "http://localhost:8080/OpenKM";  
        String username = "okmAdmin";  
        String password = "admin";  
        OKMWebservices ws = OKMWebservicesFactory.newInstance(host,  
  
        try {  
            System.out.println(ws.getAppVersion());  
        } catch (Exception e) {  
            e.printStackTrace();  
        }  
    }  
}
```


Search samples

Basics

Mosts methods use QueryParams. Here there're some tips about using them.

Variables	Type	Allow wildcards	
domain	long	No.	<p>Available values:</p> <ul style="list-style-type: none"> • QueryParams.DOCUMENT • QueryParams.FOLDER • QueryParams.MAIL <p>By default the value is set to QueryParams.I</p> <p>For searching documents and folders use va</p> <pre>(QueryParams.DOCUMENT Que</pre>
author	String	No.	Value must be a valid userId.
name	String	Yes.	
keywords	Set<String>	Yes.	
categories	Set<String>	No.	Values should be categories UUID, not use

content		Yes.	
mimeType		No.	Value should be a valid and registered MIM Only can be applied to documents node.
path		No.	When empty is used by default "/okm:root"
lastModifiedFrom	Calendar	No.	
lastModifiedTo	Calendar	No.	
mailSubject	String	Yes.	Only apply to mail nodes.
mailFrom	String	Yes.	Only apply to mail nodes.
mailTo		Yes.	Only apply to mail nodes.

<p>properties</p>	<p>Map<String, String></p>	<p>Yes on almost.</p>	<p>On metadata field values like "date" can not</p> <p>The map of the properties is composed of pairs ('metadata_field_name','metada_field_value')</p> <p>For example:</p> <pre>Map<String, String> properties = new HashMap<>(); properties.put("okp:consultation_date", "2016-01-01");</pre> <p>Filtering by range of dates:</p> <pre>Calendar to = Calendar.getInstance(); to.set(0, Calendar.HOUR); to.set(0, Calendar.MINUTE); to.set(0, Calendar.SECOND); to.set(0, Calendar.MILLISECOND); Calendar from = (Calendar) to.clone(); from.add(-3, Calendar.DATE); Map<String, String> filteredProperties = new HashMap<>(); for (Map.Entry<String, String> entry : properties.entrySet()) { filteredProperties.put(entry.getKey(), entry.getValue()); }</pre> <div style="border: 1px dashed orange; background-color: #fff9c4; padding: 5px; margin: 10px 0;">  When filtering by range of dates </div> <p>To filtering by a metadata field of type multiple:</p> <pre><select label="Multiple" name="multiple"> <option label="One" value="one">One</option> <option label="Two" value="two">Two</option> <option label="Three" value="three">Three</option> </select></pre> <p>You should do:</p> <pre>properties.put("okp:consultation_date", "one");</pre> <p>Where "one" and "two" are valid values and</p>

 The search operation is done only by AND logic.

Wildcard examples:


Variable	Example	Description
name	test*.html	Any document that start with characters "test" and ends with characters ".html"
name	test?.html	Any document that start with characters "test" followed by a single character and ends with characters ".html"
name	?test*	Any the documents where the first character doesn't matter, but is followed by the characters, "test".

Methods

findByContent

Description:

Method	Return values	Description
findByContent(String content)	List<QueryResult>	Returns a list of results filtered by the value of the content parameter.

 The method only search among all documents, it not takes in consideration any other kind of nodes.

Example:

```
package com.openkm;
import com.openkm.sdk4j.OKMWebservices;
```

```

import com.openkm.sdk4j.OKMWebservicesFactory;
import com.openkm.sdk4j.bean.QueryResult;

public class Test {
    public static void main(String[] args) {
        String host = "http://localhost:8180/OpenKM";
        String username = "okmAdmin";
        String password = "admin";
        OKMWebservices ws = OKMWebservicesFactory.newInstance(host,


        try {
            for (QueryResult qr : ws.findByContent("test")) {
                System.out.println(qr);
            }
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
}

```

findByName

Description:

Method	Return values	Description
findByName(String name)	List<QueryResult>	Returns a list of results filtered by the value of the name parameter.



The method only searches among all documents, it does not takes in consideration any other kind of nodes.

Example:

```

package com.openkm;

import com.openkm.sdk4j.OKMWebservices;
import com.openkm.sdk4j.OKMWebservicesFactory;
import com.openkm.sdk4j.bean.QueryResult;

public class Test {
    public static void main(String[] args) {
        String host = "http://localhost:8180/OpenKM";
        String username = "okmAdmin";
        String password = "admin";
        OKMWebservices ws = OKMWebservicesFactory.newInstance(host,

        try {
            for (QueryResult qr : ws.findByName("test*.html")) {
                System.out.println(qr);
            }
        }
    }
}

```


```

    }
    } catch (Exception e) {
        e.printStackTrace();
    }
}
}

```

findByKeywords

Description:

Method	Return values	Description
findByKeywords(List<String> keywords)	List<QueryResult>	Returns a list of results filtered by the values of the keywords parameter.
<div style="border: 1px dashed orange; background-color: #fff9c4; padding: 10px; display: flex; align-items: center;">  <p>The method only searches among all documents, it does not takes in consideration any other kind of nodes.</p> </div>		

Example:

```

package com.openkm;

import java.util.Arrays;

import com.openkm.sdk4j.OKMWebservices;
import com.openkm.sdk4j.OKMWebservicesFactory;
import com.openkm.sdk4j.bean.QueryResult;

public class Test {
    public static void main(String[] args) {
        String host = "http://localhost:8080/OpenKM";
        String username = "okmAdmin";
        String password = "admin";
        OKMWebservices ws = OKMWebservicesFactory.newInstance(host,
            username, password);

        try {
            for (QueryResult qr : ws.findByKeywords(Arrays.asList("
                System.out.println(qr);
            }
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
}

```

find

Description:

Method	Return values	Description
find(QueryParams queryParams)	List<QueryResult>	Returns a list of results filtered by the values of the queryParams parameter.

Example:

```

package com.openkm;

import com.openkm.sdk4j.OKMWebservices;
import com.openkm.sdk4j.OKMWebservicesFactory;
import com.openkm.sdk4j.bean.QueryParams;
import com.openkm.sdk4j.bean.QueryResult;

public class Test {
    public static void main(String[] args) {
        String host = "http://localhost:8080/OpenKM";
        String username = "okmAdmin";
        String password = "admin";
        OKMWebservices ws = OKMWebservicesFactory.newInstance(host,

        try {
            QueryParams qParams = new QueryParams();
            qParams.setDomain(QueryParams.DOCUMENT);
            qParams.setName("test*.html");

            for (QueryResult qr : ws.find(qParams)) {
                System.out.println(qr);
            }
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
}

```

findPaginated

Description:

Method	Return values	Description
findPaginated(QueryParams queryParams, int offset, int limit)	ResultSet	Returns a list of paginated results filtered by the values of the queryParams parameter.



The parameter "limit" and "offset" allow you to retrieve just a portion of the results of a query.

- The parameter "limit" is used to limit the number of results returned.
- The parameter "offset" says to skip that many results before the beginning to return results.



For example if your query have 1000 results, but you only want to return the first 10, you should use these values:

- limit=10
- offset=0

Now suppose you want to show the results from 11-20, you should use these values:

- limit=10
- offset=10

Example:

```
package com.openkm;

import com.openkm.sdk4j.OKMWebservices;
import com.openkm.sdk4j.OKMWebservicesFactory;
import com.openkm.sdk4j.bean.QueryParams;
import com.openkm.sdk4j.bean.QueryResult;
import com.openkm.sdk4j.bean.ResultSet;

public class Test {
    public static void main(String[] args) {
        String host = "http://localhost:8080/OpenKM";
        String username = "okmAdmin";
        String password = "admin";
        OKMWebservices ws = OKMWebservicesFactory.newInstance(host,
            username, password);

        try {
            QueryParams qParams = new QueryParams();
            qParams.setDomain(QueryParams.DOCUMENT);
            qParams.setName("test*.html");
            ResultSet rs = ws.findPaginated(qParams, 20, 10);
            System.out.println("Total results:"+rs.getTotal());

            for (QueryResult qr : rs.getResults()) {
                System.out.println(qr);
            }
        } catch (Exception e) {
```

```

        e.printStackTrace();
    }
}
}

```

findSimpleQueryPaginated

Description:

Method	Return values	Description
findSimpleQueryPaginated(String statement, int offset, int limit)	ResultSet	Returns a list of paginated results filtered by the values of the statement parameter.

i The **syntax** to use in the statement parameter is the pair '**field:value**'. For example:

- "name:grial" is filtering field name by word grial.

More information about Lucene sintaxis at [Lucene query syntax](#).

✓ The parameter "limit" and "offset" allow you to retrieve just a portion of the results of a query.


- The parameter "limit" is used to limit the number of results returned.
- The parameter "offset" says to skip that many results before the beginning to return results.

i For example if your query have 1000 results, but you only want to return the first 10, you should use these values:

- limit=10
- offset=0

Now suppose you want to show the results from 11-20, you should use these values:

- limit=10
- offset=10



Example:

```

package com.openkm;

import com.openkm.sdk4j.OKMWebservices;
import com.openkm.sdk4j.OKMWebservicesFactory;
import com.openkm.sdk4j.bean.QueryResult;
import com.openkm.sdk4j.bean.ResultSet;


public class Test {
    public static void main(String[] args) {
        String host = "http://localhost:8080/OpenKM";
        String username = "okmAdmin";
        String password = "admin";
        OKMWebservices ws = OKMWebservicesFactory.newInstance(host,

        try {
            ResultSet rs = ws.findSimpleQueryPaginated("name:grial"
            System.out.println("Total results:"+rs.getTotal());

            for (QueryResult qr : rs.getResults()) {
                System.out.println(qr);
            }
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
}
    
```

findMoreLikeThis

Description:

Method	Return values	Description
findMoreLikeThis(String uuid, int max)	ResultSet	Returns a list of documents that are considered similar by the search engine.
<p>The uuid is a document UUID.</p> <p>The max value is used to limit the number of results returned.</p>		
<div style="border: 1px dashed orange; padding: 10px; background-color: #fff9c4;">  <p>The method can only be used with documents.</p> </div>		

Example:

```

package com.openkm;

import com.openkm.sdk4j.OKMWebservices;
import com.openkm.sdk4j.OKMWebservicesFactory;
import com.openkm.sdk4j.bean.QueryResult;
import com.openkm.sdk4j.bean.ResultSet;

public class Test {
    public static void main(String[] args) {
        String host = "http://localhost:8080/OpenKM";
        String username = "okmAdmin";
        String password = "admin";
        OKMWebservices ws = OKMWebservicesFactory.newInstance(host,

        try {
            ResultSet rs = ws.findMoreLikeThis("f123a950-0329-4d62-
            System.out.println("Total results:"+rs.getTotal());

            for (QueryResult qr : rs.getResults()) {
                System.out.println(qr);
            }
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
}

```

getKeywordMap

Description:

Method	Return values	Description
getKeywordMap(List<String> filter)	Map<String, Integer>	Returns a map of keywords with its count value filtered by other keywords.

i Example:

- Doc1.txt has keywords "test", "one", "two".
- Doc2.txt has keywords "test", "one"
- Doc3.txt has keywords "test", "three".

The results filtering by "test" -> "one", "two", "three".

The results filtering by "one" -> "test", "two".

The results filtering by "two" -> "test", "one".

The results filtering by "three" -> "test".

The results filtering by "one" and "two" -> "test".

Example:

```

package com.openkm;

import java.util.ArrayList;
import java.util.Arrays;
import java.util.Map;

import com.openkm.sdk4j.OKMWebservices;
import com.openkm.sdk4j.OKMWebservicesFactory;

public class Test {
    public static void main(String[] args) {
        String host = "http://localhost:8180/OpenKM";
        String username = "okmAdmin";
        String password = "admin";
        OKMWebservices ws = OKMWebservicesFactory.newInstance(host,

        try {
            // All keywords without filtering
            System.out.println("Without filtering");
            Map<String, Integer> keywords = ws.getKeywordMap(new Ar

            for (String key : keywords.keySet()) {
                System.out.println(key + " is used :" + keywords.ge
            }

            // Keywords filtered
            System.out.println("Filtering");
            keywords = ws.getKeywordMap(Arrays.asList("test"));

            for (String key : keywords.keySet()) {
                System.out.println(key + " is used :" + keywords.ge
            }
        } catch (Exception e) {
            e.printStackTrace();
        }
    }
}
    
```

getCategorizedDocuments

Description:

Method	Return values	Description
getCategorizedDocuments(String	List<Document>	Retrieves a list of all documents

categoryId)		related with a category.
The values of the categoryId parameter should be a category folder UUID or path.		

Example:

```
package com.openkm;  
  
import com.openkm.sdk4j.OKMWebservices;  
import com.openkm.sdk4j.OKMWebservicesFactory;  
import com.openkm.sdk4j.bean.Document;  
  
public class Test {  
    public static void main(String[] args) {  
        String host = "http://localhost:8180/OpenKM";  
        String username = "okmAdmin";  
        String password = "admin";  
        OKMWebservices ws = OKMWebservicesFactory.newInstance(host,  
  
        try {  
            for (Document doc : ws.getCategorizedDocuments("/okm:ca  
                System.out.println(doc);  
            }  
        } catch (Exception e) {  
            e.printStackTrace();  
        }  
    }  
}
```